



شرکت ویستا پلیمر مهر
(سهامی خاص)
Vista Polymer Mehr Co

White Master batch

White Polyethylene Master batch

مستر بیچ پلی اتیلن سفید

BM 226 C

Description:

- White Blue Masterbatch
- Active Ingredient: Organic and Aluminum Treated TiO₂ (Approx. 65%)

Applications

- Heavy Duty FFS Polyethylene PE
- High Gloss and Shiny White Packaging Films
- High Gloss and Shiny White Shopping Films
- 3 Layer Polyethylene Films (Recommended for Out Layer)
- Recommended Dosage: 3 ~ 8%

Advantages:

- High Gloss of Film's
- High Opacity of Film's
- Without Calcium Carbonate

Technical Properties

Properties	Test Method	Unit	Value
Ash Content	ASTM D2584	%	72±2
Melt Flow Rate	ASTM D1238	gr/10 min	8±2
Melt Density (in MFI test)	ASTM D1238	gr/cm ³	1.51
Granulate Size	-	mm	2 ~ 4
Contamination		No. Defects in 200 gr of pellets	≤5

Package:

Packed in 25Kg PP bags or 1375 Kg Jumbo bag

Transportation:

Avoid from sunlight, moisture and crash.

Address: Tabriz, Tabriz Azarshahr Road, west industrial zone

No.123

Tel: 0098 4132459296

Fax: 0098 4132459297

Website: www.polymervista.ir

Email: info@polymervista.ir

آدرس: تبریز، جاده تبریز - آذرشهر، شهرک صنعتی غرب تبریز پلاک ۱۲۳

تلفن: ۰۴۱-۳۲۴۵۹۲۹۶

فکس: ۰۴۱-۳۲۴۵۹۲۹۷